

CP- UNR-408T2-P8

8 Ch. Network Video Recorder with 8 PoE Ports



Main Features

- 8 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance, 8 PoE Ports
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-408T2-P8

8 Ch. Network Video Recorder with 8 PoE Ports

Feature

Processor
 Operating System
 IP Camera Input
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Smart Phone
 Hard Disk
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Record Interval
 Max User Account
 Interface Ports
 Ethernet
 Protocols
 Power Supply
 Power Consumption

Specification

Dual-core embedded processor
 Embedded LINUX
 8 channel
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.264 / MJPEG
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Max 128 Mbps
 1/4/8/9
 MD Zones: 396(22×18).
 Supports
 Supports
 4 channel
 2 channel
 iPhone, iPad, Android, Windows Phone
 2 SATA ports (2HDDs), up to 8TB, Raid (redundancy)
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Internal SATA burner/ Network
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 128 users
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45
 1 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.2
 Single, AC 100~240V, 50/60 Hz
 NVR: 20W(without HDD), PoE: Max 25.5W for single port

CP- UNR-408T2-P8

8 Ch. Network Video Recorder with 8 PoE Ports

Feature

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm × 285mm × 50mm

2.5 Kg (without HDD)



1141 Budapest, Fogarasi út 77.
Tel.: *220-7940, 220-7814, 220-7959,
220-8881, 364-3428 Fax: 220-7940
Mobil: 30 531-5454, 30 939-9989

1095 Budapest, Mester u. 34.
Tel.: *218-5542, 215-9771, 215-7550,
216-7017, 216-7018 Fax: 218-5542
Mobil: 30 940-1970, 20 949-2688

www.cpplus.hu

E-mail: info@delton.hu Web: www.delton.hu