

CP- UNR-416T2

16 Ch. Network Video Recorder



Main Features

- 16 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview & playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



CP- UNR-416T2

16 Ch. Network Video Recorder

Feature

Processor
 IP Camera Input
 Operating System
 Two-way Talk
 User Interface
 Video Output
 Compression
 Video Resolution
 Video Recording
 Video Display Split
 Motion Detection
 Video Loss
 Camera Blank
 Alarm Input
 Alarm Output
 Hard Disk
 Smart Phone
 Trigger Events
 Recording Mode
 Search Mode
 Playback
 Backup Mode
 Max User Account
 Interface Ports
 Record Interval
 Ethernet
 Protocols
 Power Supply
 Power Consumption

Specification

Dual-core embedded processor
 16 channel
 Embedded LINUX
 1 channel Input, 1 channel Output, RCA
 GUI
 1 HDMI, 1 VGA
 H.264 / MJPEG
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
 Max 128 Mbps
 1/4/8/9/16
 MD Zones: 396(22×18).
 Supports
 Supports
 4 channel
 2 channel
 2 SATA ports, up to 8TB, Raid (Redundancy)
 iPhone, iPad, Android, Windows Phone
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
 Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
 USB Device / Internal SATA burner/ Network
 128 users
 1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45
 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
 1 RJ-45 port (10/100M/1000M)
 HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3
 DC12V/4A
 20W(without HDD)

CP- UNR-416T2

16 Ch. Network Video Recorder

Feature

Working Temp

Dimensions

Weight

Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm×285mm×50mm

2 Kg (without HDD)



1141 Budapest, Fogarasi út 77.
Tel.: *220-7940, 220-7814, 220-7959,
220-8881, 364-3428 Fax: 220-7940
Mobil: 30 531-5454, 30 939-9989

1095 Budapest, Mester u. 34.
Tel.: *218-5542, 215-9771, 215-7550,
216-7017, 216-7018 Fax: 218-5542
Mobil: 30 940-1970, 20 949-2688

www.cpplus.hu

E-mail: info@delton.hu Web: www.delton.hu