

# CP- UNR-432T2

## 32 Ch. Network Video Recorder



### Main Features

- 32 Ch. with 1080p Realtime Live View
- H.264/MJPEG dual codec decoding
- Up to 5Mp resolution preview&playback
- Max 200Mbps incoming bandwidth
- Support 2 SATA HDDs up to 8TB, 2 USB2.0
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.3 conformance
- Mobile Software: iCMOB, gCMOB, wCMOB
- CMS Software: KVMS, KVMS Pro



# CP- UNR-432T2

## 32 Ch. Network Video Recorder

### Feature

Processor  
 Operating System  
 IP Camera Input  
 Two-way Talk  
 User Interface  
 Video Output  
 Compression  
 Video Resolution  
 Video Recording  
 Video Display Split  
 Motion Detection  
 Video Loss  
 Camera Blank  
 Alarm Input  
 Alarm Output  
 Hard Disk  
 Smart Phone  
 Trigger Events  
 Recording Mode  
 Search Mode

### Specification

Dual-core embedded processor  
 Embedded LINUX  
 32 channel  
 1 channel Input, 1 channel Output, RCA  
 GUI  
 1 HDMI, 1 VGA  
 H.264 / MJPEG  
 2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768  
 Max 128 Mbps  
 1/4/8/9/16  
 MD Zones: 396(22×18).  
 Supports  
 Supports  
 4 channel  
 2 channel  
 2 SATA ports, up to 8TB, Raid (Redundancy)  
 iPhone, iPad, Android, Windows Phone  
 Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen  
 Manual, Schedule(Regular(Continuous), MD, Alarm), Stop  
 Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Playback

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

Backup Mode

USB Device / Internal SATA burner/ Network

Interface Ports

1 HDMI, 1 VGA, 2 USB2.0, 1 RS485, 1 RS232, 1 RJ45

Record Interval

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

Max User Account

128 users

Ethernet

1 RJ-45 port (10/100M/1000M)

Protocols

HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, ONVIF Version 2.3

Power Supply

DC12V/4A

Power Consumption

20W(without HDD)

# CP- UNR-432T2

## 32 Ch. Network Video Recorder

### Feature

Working Temp

Dimensions

Weight

### Specification

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm×285mm×50mm

2 Kg (without HDD)



**1141 Budapest, Fogarasi út 77.**  
Tel.: \*220-7940, 220-7814, 220-7959,  
220-8881, 364-3428 Fax: 220-7940  
Mobil: 30 531-5454, 30 939-9989

**1095 Budapest, Mester u. 34.**  
Tel.: \*218-5542, 215-9771, 215-7550,  
216-7017, 216-7018 Fax: 218-5542  
Mobil: 30 940-1970, 20 949-2688

**[www.cpplus.hu](http://www.cpplus.hu)**

E-mail: [info@delton.hu](mailto:info@delton.hu) Web: [www.delton.hu](http://www.delton.hu)