

CP-YPS-PD20-12D

Plastic Case Desktop Power Supply



Feature	Specification
Input voltage	AC100-240V50/60Hz 0.5A
Output Connector	55 x 21mm DC Plug
Output voltage	12V DC
Output electric current	2000MA
Ripple wave	(mVp-p): <1%
Linear modulate	±0.5%max
Temperature	±0.02%/°C
start time	≤1s(240V output,1o=100%)
guard time	≥20ms(240V input,1o=100%)
short-circuit	1 channel: automatic recovery
override protection	115%~150%kVA,automatic recovery
overvoltage protection	30%~150%V AC, automatic recovery
working temperature	0°C~40°C,10%~90%RH
Store temperature	-20°C~85°C,10%~90%RH
Dimension	103 x 55 x 34mm
Weight	140g



1141 Budapest, Fogarasi út 77. 1095 Budapest, Mester u. 34.
 Tel.: *220-7940, 220-7814, 220-7959, Tel.: *218-5542, 215-9771, 215-7550,
 220-8881, 364-3428 Fax: 220-7940 216-7017, 216-7018 Fax: 218-5542
 Mobil: 30 531-5454, 30 939-9989 Mobil: 30 940-1970, 20 949-2688

www.cpplus.hu

E-mail: info@delton.hu Web: www.delton.hu