

Stand alone

With numeric keypad

Extruded aluminium module.

Numeric keypad with stainless steel covered buttons.

Dimensions: external: 134(W) x 148(H) mm.
empotrado: 125(W) x 140(H) x 56(D) mm.

Stand alone access control module.

System programming through the keypad, with acoustic acknowledgement signal on push.

2 output relays with 8 activation codes each one and an independent panic code.

4, 5 or 6 digits programmable codes.

One code can be used to activate more than one relay.

Relay 1: n/c or n/o, single shoot or stable software programmable.

Relay 2: single shoot with three contacts (n/c or n/o).

Programmable activation time from 0 to 20 seconds in single shoot mode.

After introduction of 3 wrong consecutive codes, in a period of less than 15 seconds, the access control is disabled during 3 minutes. After this time, if 3 wrong consecutive codes are introduced again, the disabled time is doubled up to a maximum of 12 minutes.

12Vd.c. battery input without charge management.

Access control module accessories are detailed on page 27.



4301/AL

Access control kit composed of:

11284301

3301/AL access control module.	p. 58
600/AL closing heads.	p. 49
CE610 embedding box.	p. 50
TF-104 transformer.	p. 59
CV-14 lock release.	p. 78

With proximity reader

Extruded aluminium module.

Dimensions: external: 134(W) x 148(H) mm.
embedded: 125(W) x 140(H) x 56(D) mm.

Stand alone access control module.

7cm. reading distance using PROXCARD or NEOKEY proximity tags (pag. 27).

Up to 500 users in one or several memory addresses.

System programming through the internal keypad. A PIN code is required for system management.

Seven segments memory display.

1 output single shoot relay of 3 seconds activation time.

Access control module accessories are detailed on page 27.



4502/AL

Access control kit composed of:

11284502

N Proximity reader module.	
600/AL closing heads.	p. 49
CE610 embedding box.	p. 50
6 units of PROXCARD proximity ISO card.	p. 27
TF-104 transformer.	p. 59
CV-14 lock release.	p. 78

Stand alone

Accessories

	711/AL	Rain shield.	11280711	p. 51	
	871/AL	Surface box with integrated rain shield.	11280871	p. 50	
	881/AL	Surface box.	11280881	p. 51	
		<p>N ! Cannot be used with rain shield. Does not use embedding box. 32 mm. depth only. Dimensions: 134(W) x 148(H) x 32(D) mm. Available from 1st quarter 2006.</p>			
	911/AL	45° surface box.	11280911	p. 53	
	611/AL	Replacement frame.	11280611	p. 54	
		<p>Covers the existing hole from larger panels. Dimensions: 200(W) x 278(H) mm.</p>			
	NEOKEY	Key holder proximity tag.	20760401		
		<p>Dimensions: 36(W) x 47(H) x 11(D) mm.</p>			
	PROXCARD	Proximity ISO card.	20750504		
		<p>Dimensions: 43(W) x 75(H) mm.</p>			

With audio

Available with Platea T-712VD telephone from 2nd quarter 2006

Extruded aluminium panel.

Electronic call with acoustic acknowledgement signal at the door panel.

Steady illumination at the door panel.

Numeric keypad with stainless steel covered buttons.

Dimensions: external: 134(W) x 265(H) mm.

empotrado: 125(W) x 257(H) x 56(D) mm.

Includes access control with numeric keypad (see characteristics on pag. 26).

4+'n' installation, which allows up to 3 telephones inside the same apartment (pag. 62 and 66).

These kits include a telephone (T-902) with an additional push button with potential free contact.

To be used with 12Va.c. lock releases (pag. 78 and 79).

Door panel accessories are detailed on page 29.

Schematic diagrams and sections chart are shown on page 94.



4113/AL

1 way audio kit composed of:

11284113

N	<ul style="list-style-type: none"> 2110/AL one push button grille module. p. 46 Sound module. 3301/AL access control module. p. 58 600/AL closing heads. p. 49 CE610 embedding box. p. 50 Condal T-902 telephone with electronic call. p. 66 TF-104 transformer. p. 59
---	---



x 2

4223/AL

2 ways audio kit composed of:

11284223

N	<ul style="list-style-type: none"> 2220/AL two push buttons grille module. p. 46 Sound module. 3301/AL access control module. p. 58 600/AL closing heads. p. 49 CE610 embedding box. p. 50 2 units of Condal T-902 telephone with electronic call. p. 66 TF-104 transformer. p. 59
---	---

With Audio

Accessories



721/AL

Rain shield.

11280721

p. 51

872/AL

Surface box with integrated rain shield.

11280872

N

Does not use embedding box.
32 mm. depth only.

p. 50



882/AL

Surface box.

11280882

N !

Cannot be used with rain shield.

p. 51

Does not use embedding box.
32 mm. depth only.
Dimensions: 134(W) x 265(H) x 32(D) mm.
Available from 1st quarter 2006.

921/AL

45° surface box.

11280921

Dimensions: 140(W) x 231(H) x 140(D) mm.

p. 53



621/AL

Replacement frame.

11280621

Covers the existing hole from larger panels.
Dimensions: 200(W) x 395(H) mm.

p. 54