

SANAN SA-1322CM



* CMOS Megapixel;
* 1.3 megapixel live display, 2.0 mega pixel not real time(15 ft);
* Standard H.264 Main Profile Code, Dual Code Stream;
* SD Card Storage;
* Water and Dust proof Casing, Support IP66 Standard;
* 48 pieces of LED, IR Distance 50 meters;
* Embedded mini watt WiFi module(Wireless Distance 100 meters).

Model	SA-1322CM
Image Sensor	1/3 inch CMOS
Minimum Illumination	0.5 Lux
Lens Included	6mm,8mm and 12mm mega pixels for optional
Infrared Light	48 Infrared light
IR Distance	30~50m
Sensitivity	Color:0.3Lux; B&W:0.01Lux; Infrared:0Lux
Video Compression	H.264 Main Profile@Level 3
Video Resolution	CMOS:1600 x 1200, 1280x960, 1280 x 720
Video Parameters	Brightness, hue, contrast, saturation and image quality

Two Streaming	Preferred stream and Alternate stream: H.264 & MJPEG
Streaming Format	Video Streaming or Audio & Video composite Streaming
Video Frame Rate	1600 x 1200: 1~15 frames/second
	1280 x 960: 1~25 frames/second
	1280 x 720: 1~30 frames/second
Video Compression Bit rate	32Kbit/S~16Mbit/S
Audio Input	1channel, linear input, Input Impedance:1KOhms
Audio Compression	G.726, G.711
Audio Output	1channel, linear output
Two-way talk Input	Support Audio two-way talk
Overlaid Caption	Channel, Date, Bit rate, position adjustable
Local Recording	SD card slot (maximum 32GB SD card supported)
Supported Protocols	TCP, UDP, IP, HTTP, FTP, SMTP, DHCP, DNS, ARP, ICMP, POP3, NTP, Ipsec, UpnP, RTP, RTCP, RTSP and so on
System Interface	10Base-T/100Base-TX Ethernet port
	WiFi(802.11B/G) built-in
	Support FTP
	1 RS485
IP Degree	IP66
Alarm Input	1channel on/off input, Support NO (open) or NC (closed)
Alarm Output	1 channel on/off, 120VAC 1A/24VDC 1A
Alarm Message	Sending alarm message by Email
Power Supply	DC 12V 3A
Power Consumption	Less than 10W
Work Temperature	-10°C ~ +55°C
Storage Temperature	-20°C ~ +70°C
Work Humidity	10~85%
Computer System Requirements	OS: Microsoft Windows 98/ME/2000/XP/2003/Vista/Windows 7
	IE: Microsoft Internet Explorer version 6, 7 or 8
Product Dimension(mm)	270x95x105mm

Package Box (1pc)	325x170x240mm
Carton Packing (10pcs)	800x350x250mm