

SANAN SA-1516



* Image Sensor	1/3" SONY Super HAD CCD;
* Resolution	420TVL, 540TVL(Optional);
* Lens	3.6mm Board Lens(6mm/8mm Optional);
* LED	∅ 5mm×30PCS;
* IR Distance	30m;
* Waterproof	IP66;
* Bracket	3 Axis Bracket.

Model	SA-1516	
Image Sensor	1/3" Sony Super HAD CCD	
TV System	PAL/NTSC	
Effective Pixel	PAL:500(H)×582(V) NTSC:510(H)×492(V)	PAL:752(H)×582(V) NTSC:768(H)×494(V)
Horizontal Resolution	420TVL	540TVL
Minimal Illumination	0.1Lux/F1.2 0Lux(IR On)	
Synchronous System	Internal Synchronization	
S/N Ratio	>48dB	
Electronic Shutter	1/50-1/60,000s(PAL) 1/60-1/60,000s(NTSC)	
White Balance	ATW	
BLC	On	
AGC	Auto	
Gamma Adjusting	0.45	
Video Output	1.0Vp-p at 75Ω	
Lens	3.6mm Board Lens(6mm/8mm Optional)	

LED	∅ 5mm×30PCS
IR Distance	30m
Power Supply	DC 12V
Working Temperature	-10°C~+50°C RH90% MAX
Dimension(mm)	170mm×69mm×65mm
Weight(g)	300g