

SANAN SA-1524



| | |
|----------------|--|
| * Image Sensor | 1/3" SONY Color CCD; |
| * Resolution | 600TVL; |
| * Lens | 4-9mm Varifocal lens; |
| * LED | ∅ 5mm×24PCS; |
| * IR Distance | 30m; |
| * Bracket | All-Oriented Bracket with Cable Concealed; |
| * Waterproof | IP66; |
| * OSD Menu | OSD Menu with Various Functions; |
| * Other | 3-DNR, IR cut Function. |

| Model | | SA-1524 |
|-----------------------|-------|--|
| Image Sensor | | 1/3" Sony Color CCD |
| TV System | | PAL/NTSC |
| Horizontal Resolution | | 600TVL |
| Minimal Illumination | | 0Lux(IR On) |
| Synchronous System | | Internal Synchronization |
| S/N Ratio | | ≥50dB(AGC Off) |
| Sense Up | | 4Time; 8Time; 16Time; 32Time; 64Time; 128Time; 256Time;Off |
| Electronic Shutter | | 1/50-1/100,000s(PAL) 1/60-1/100,000s(NTSC) |
| White Balance | Mode | Manual, Auto Tracing; Auto |
| | Range | (Auto)2200~10,000° K |
| BLC | | On; Off; Hard Light Suppression |
| AGC | | Low; Middle; High; Off |
| Iris Control | | Iris DC |

| | |
|-----------------------------------|---|
| Day/Night | Auto; Color turn to Black and White |
| Mirror | Horizontal; Vertical; Whirl |
| Lens | 4-9mm Varifocal Lens |
| LED | ∅ 5mm×24PCS |
| IR Distance | 30m |
| Motion Detection | On/Off |
| Privacy | On/Off |
| Adjustment | Brightness Adjustment, Sharpness Adjustment |
| Title | On/Off (Max 15 Characters) |
| 3-DNR | On/Off |
| Digital Wide Dynamic Range | Off; Indoor; Outdoor |
| Power Supply | DC 12V or AC 24V / 400mA |
| Waterproof | IP66 |
| Working Temperature | -10°C~+50°C |
| Storage Temperature | -20°C~+60°C |
| Dimension(mm) | 275mm×85mm×110mm |
| Weight(g) | 900g |