

SANAN SA-2604B/SA-2608B/SA-2616B



Specification

- * Full new aluminum alloy drawbench panels
- * Built-in 4.3LCD monitor
- * Stand Alone DVR, H.264 Compression
- * Local operation: Mouse, Remote, 4.3LCD Touch Screen
- * High quality video Display : NTSC (720x480), PAL (704x576) real time, display D1
- * Multiple Recording/ Search Categories: Date/Time, Event, Manual, Schedule, alarm, motion detection
- * Real time recording support: 120 Fps for NTSC at CIF image (100 Fps for PAL)
- * Pentaplex: Live, Record, Playback, Back-up and Network at the same time
- * Backup: CD-RW (Option: DVD-RW), USB 2.0 and NET backup supported
- * PTZ camera control in local and remote area
- * E-mail notification
- * 3G support

Model	A-2604B	SA-2608B	SA-2616B
Video Input	4 Channel, BNC , 1.0p-p/75Ω	8 Channel, BNC, 1.0p-p/75Ω	16 Channel, BNC, 1.0p-p/75Ω
Composite Video Output	2 CH, BNC , 1.0V p-p/75Ω, 1 Channal VGA output	1 CH, BNC , 1.0V p-p/75Ω, 1 Channal VGA output	
Audio Output	2 Channel		1 Channel

Alarm Input	2 Channel	4 Channel
Alarm Output	1 Channel	4 Channel
Alarm Mode	Sensor Input, Motion Detection, Video Loss, Full Disk Space.	
Network	Ethernet (10/100M)、LAN、WAN and ADSL	
Control Way	USB2.0 Mouse, Remote Control, PTZ, Camera, RS485 x 1	
Backup	USB2.0, CDRW, DVDRW and Network	
Bit Rate	5 Levels: 120MB/H, 150MB/H, 250MB/H	
Password	Encrypted by 128-bit Numerical Digits with 2-Level Password Protection	
Compression Standard	H. 264	
Hard disk	2T Hard disk × 2pcs	
Power Supply	DC12V/3A	
Consumption	10W(Without hard disk)	
Working Temperature	-10°C~+60°C; humidity: < 90%	
Storage Temperature	-20°C~+60°C; humidity: < 95%	
Size	431×267×77.3(mm)	
Package Size	470×350×175(mm)	
Weight	N.W:3.8kg	G.W:5kg