

## SANAN SA-1523



|                       |  |
|-----------------------|--|
| * <b>Image Sensor</b> | 1/3" SONY Color CCD;                       |
| * <b>Resolution</b>   | 450TVL, 520TVL, 600TVL(Optional);          |
| * <b>Lens</b>         | 8-20mm Varifocal lens;                     |
| * <b>LED</b>          | ∅ 5mm×56PCS;                               |
| * <b>IR Distance</b>  | 60m;                                       |
| * <b>Bracket</b>      | All-Oriented Bracket with Cable Concealed; |
| * <b>Waterproof</b>   | IP66;                                      |
| * <b>OSD Menu</b>     | OSD Menu with Various Functions;           |
| * <b>Other</b>        | 3-DNR, IR cut Filter.                      |

| Model                 |       | SA-1523                                       |
|-----------------------|-------|---|
| Image Sensor          |       | 1/3" Sony Color CCD                           |
| TV System             |       | PAL/NTSC                                      |
| Horizontal Resolution |       | 600TVL(520TVL,450TVL Optional)                |
| Minimal Illumination  |       | 0Lux(IR On)                                   |
| Synchronous System    |       | Internal Synchronization                      |
| S/N Ratio             |       | ≥50dB(AGC Off)                                |
| Electronic Shutter    |       | 1/50-1/100,000s(PAL)<br>1/60-1/100,000s(NTSC) |
| White Balance         | Mode  | Manual, Auto Tracing; Auto                    |
|                       | Range | (Auto)2200~10,000° K                          |
| BLC                   |       | On:64 area BLC; Off                           |
| AGC                   |       | Low; Middle; High; Off                        |

|                            |                                     |
|----------------------------|-------------------------------------|
| <b>Iris Control</b>        | Iris DC                             |
| <b>Day/Night</b>           | Auto; Color turn to Black and White |
| <b>Lens</b>                | 8-20mm Varifocal lens               |
| <b>LED</b>                 | ∅ 5mm×56PCS                         |
| <b>IR Distance</b>         | 60m                                 |
| <b>IR CUT</b>              | Auto                                |
| <b>Motion Detection</b>    | LED Warning                         |
| <b>Power Supply</b>        | DC 12V or AC 24V / 750mA            |
| <b>Waterproof</b>          | IP66                                |
| <b>Working Temperature</b> | -10°C~+50°C                         |
| <b>Storage Temperature</b> | -20°C~+60°C                         |
| <b>Dimension(mm)</b>       | 275mm×86mm×110mm                    |
| <b>Weight(g)</b>           | 1400g                               |