

MANUAL INSTALLATION

IS 210 / IS 211 / IS 320 / IS 322

INDOOR SOUNDER




eds IS 210 / IS 211 / IS 320 / IS 322
INDOOR SOUNDER

General


High sound level. Compatible with all kind of alarm/fire panels.
IS 210 and IS 211 have the tamper switch for sabotage.
Stylish design and easy using. Indoor applications.

Technical Specifications

Model	IS 210	IS 211	IS 320	IS 322
Application area	Security		Fire	
Operating voltage	12VDC		24VDC	
Frequency for sound 1	3334Hz			
Frequency for sound 2	2250-3400Hz			
Sound output	min.100dB (1m)		min.95dB (1m)	
Alarm current	160mA		45mA	
LED Indicator	Single	Triplet	Single	Triplet
Tamper	Available		-	
Output	Terminate blocks			
Environment	Indoor			
Housing	ABS plastic			
Color of housing	White		Red	
Dimensions (mm)			110 x 110 x 40	
Weight	125gr		112gr	
Operating temperature	-10°C ~ +55°C			



Connections



CONNECTION TYPE

Model	Sound	VDD	GND
IS 210 IS 211	FOR SOUND 1	VDD +12V	GND 1 0V
	FOR SOUND 2	VDD +12V	GND 2 0V
IS 320 IS 322	FOR SOUND 1	VDD +24V	GND 1 0V
	FOR SOUND 2	VDD +24V	GND 2 0V

Note:

A,B,C & D holes for the cable entry.
Mount optionally provided A,B,C,D,E,F holes.