MIO-C



▶ B TTERY AND OPENING OF THE REMOTE CONTROL [1]


Open the case with a screwdriver removing fixing screw **A**. When the battery is replaced, check the polarity. Keep the battery away from children. Dispose of the old battery in the correct manner and according to your local regulations.

► CODE GENERATION [2]

The first button of remote control will already have a code assigned (created by NOLOGO during testing) and the second button has no code assigned. This operation creates new codes for both buttons and cancels the previous codes.

- Press button no.1 and then button no.2 and keep them pressed.
- The light **B** flashes slowl .
- Wait 8 seconds until the light is flashin faster.
- Let go of button no.1 and after a moment button no.2

Now every button has a generated code from millions of different combinations.



- ▶ HOW TO LEARN A CODE [3 4]
- Press button no.1 and then button no.2 and keep them pressed.
- The light **B** starts flashin
- Release the button which is not to be copied on to.
- Press the original transmitter's button X which you want to copy
- Keep the two remote controls close to each other as shown in picture no.4, so that the antenna of the original remote control X, usually in the bottom part of the remote control(check it by opening the remote control) should be as near as possible to the receiving part C of the MIO-C

The light **B** flashes rapidly for a while and then it flashes regularly to confirm that the code has been copied.

